Product datasheet

Specification





Kaedra - for power outlet - 6 openings - 1 x 12 modules

13181

Main

Range	Mureva
Product Name	Mureva Enclosure
Product Or Component Type	Weatherproof enclosure
Enclosure Type	Enclosure for power outlet
Mounting Plate Description	Without mounting plate

Complementary

• • · · · · · · · · · · · · · · · · · ·	
Enclosure Mounting	Surface
9 Mm Pitches	24
Number Of 18 Mm Modules Per Row	12
Total Number Of 18 Mm Modules	12
Number Of Horizontal Rows	1
Electrical Insulation Class	Class II Double insulation
Number Of Openings Of Interface	6
Number Of Plates	2 for push-button controls 6 for 65 x 85 power outlets
Provided Equipment	2 wiring strap 6 plate for 65 x 85 power outlet 2 plate for push-button control
Type Of Front Cover	Transparent
Power Dissipation In W	28 W
[In] Rated Current	63 A
Type Of Rail	DIN
Number Of Pre-Cutouts Pg Iso	17
Locking Options Description	Optional keylock
Enclosure Material	Housing: self-extinguishing polymer
Net Weight	2.5 kg
Base Dimension	90 x 100 mm
Width	340 mm
Height	460 mm
Depth	160 mm
Internal Depth	91 mm

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.



Colour Door: transparent green
Enclosure: light grey (RAL 7035)

Environment

Standards	IEC 61439-3 IEC 60695-2-1 IEC 60670 EN 62262 EN 50262
Fire Resistance	650 °C conforming to IEC 60695-2-1
Ip Degree Of Protection	IP65 conforming to IEC 60529
Ik Degree Of Protection	IK09 conforming to EN 50102
Environmental Characteristics (Uv)	UV resistant: class 3 conforming to ISO 4582:2010 Ultraviolet degradation test conforming to ISO 4892-2:2013
Overvoltage Category	II
Ambient Air Temperature For Operation	-2540 °C

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	16.8 cm
Package 1 Width	36.0 cm
Package 1 Length	47.0 cm
Package 1 Weight	2.848 kg
Unit Type Of Package 2	P12
Number Of Units In Package 2	28
Package 2 Height	80.0 cm
Package 2 Width	80.0 cm
Package 2 Length	120.0 cm
Package 2 Weight	91.744 kg

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >







Lower Impact Materials Transparency RoHS/REACh

Resource performance

Minimum Percentage Of Recycled Plastic Content 25

Well-being performance

Reach Free Of Svhc

Toxic Heavy Metal Free

Mercury Free

Rohs Exemption Information Yes

Halogen Free Product

Certifications & Standards

Reach Regulation

REACh Declaration

Pro-active compliance (Product out of EU RoHS legal scope)

EU RoHS Declaration

China Rohs Regulation

China RohS declaration

Pro-active China RoHS declaration (out of China RoHS legal scope)

Environmental Disclosure

Product Environmental Profile

No need of specific recycling operations